

Bibliographie Labo 2025

- [1] K. Bourkaib *et al.*, « Comparative Study of Opuntia ficus-indica Polymers, HPAM, and Their Mixture for Enhanced Oil Recovery in the Hassi Messaoud Reservoir, Algeria », *Processes*, vol. 13, n° 6, p. 1794, juin 2025, doi: 10.3390/pr13061794.
- [2] S. B. Tchinwoussi Youbi *et al.*, « Effect of NaOH and silane treatment on short Raphia vinifera fiber bio-epoxy composites », *Int. J. Polym. Anal. Charact.*, vol. 0, n° 0, p. 1-21, oct. 2025, doi: 10.1080/1023666X.2025.2575782.
- [3] N. Defo *et al.*, « Effect of the surface energy of vegetable shells and hard cores on the adhesion and tribological properties of agglomerated bio-based grinding wheels », *Wear*, vol. 564-565, p. 205736, mars 2025, doi: 10.1016/j.wear.2025.205736.
- [4] T. O. A. Adegoon *et al.*, « Elaeis Guineensis OPMF as a Green Alternative Source of Cellulose Pulp Fibers for the Textile and Composite Industries », *J. Text. Inst.*, vol. 0, n° 0, p. 1-22, juin 2025, doi: 10.1080/00405000.2025.2510902.
- [5] H. Shen, J. Zhao, S. Xiao, et P. Wang, « Exploring deformability in 3D tufted composite reinforcements: Understanding bending behaviors in forming applications », *Compos. Struct.*, vol. 354, p. 118753, janv. 2025, doi: 10.1016/j.compstruct.2024.118753.
- [6] B. Camillieri, J. Faucheu, R. Ackerley, N. Le Moing, et M.-A. Bueno, « Influence of finger movement direction on friction-induced vibrations and perception of textured surfaces », *Tribol. Int.*, vol. 211, p. 110844, nov. 2025, doi: 10.1016/j.triboint.2025.110844.
- [7] Y. Wang, X. Li, S. Krugl, et P. Wang, « Innovative yarn modeling with fiber damage for predicting friction and wear in textile reinforcement manufacturing », *Tribol. Int.*, vol. 212, p. 110956, déc. 2025, doi: 10.1016/j.triboint.2025.110956.
- [8] B. Schrab, A. Collaine, J.-M. Freyburger, et M. Tournalias, « Machinability analysis of UD-GFRP composites in edge trimming with diamond-coated burr tools at various fiber orientations », *CIRP J. Manuf. Sci. Technol.*, vol. 59, p. 194-206, juill. 2025, doi: 10.1016/j.cirpj.2025.03.008.
- [9] A. MAMANE, S. Giljean, B. GACHET, C. FRANCOIS, G. Lhostis, et M.-J. Pac, « Measurement of residual stresses in fiber-reinforced composites by the incremental hole drilling method: effect of the drilling-induced heating. », mai 2025, doi: 10.21203/rs.3.rs-6734213/v1.
- [10] M. Hussein, D. Mathieu, G. L'hostis, et B. Durand, « Modulated quasi-static tensile testing for advanced characterization of elastomer mechanics », *Polym. Test.*, vol. 147, p. 108825, juin 2025, doi: 10.1016/j.polymertesting.2025.108825.
- [11] M. Hussein, D. Mathieu, G. L'hostis, et B. Durand, « Monitoring of Thermal and Deformation Fields of a Textile Subjected to Modulated Quasi-Static Tensile Test Using a Thermal Camera », *Exp. Mech.*, nov. 2025, doi: 10.1007/s11340-025-01247-1.
- [12] B. G, A.-M. R, D. Jy, P. C, K. S, et T. W, « New Weaving Machine Structure based on Motion Control System - Textile Science Engineering Journal | Fashion Technology », Consulté le: 12 janvier 2026. [En ligne]. Disponible sur: <https://juniperpublishers.com/ctftte/CTFTTE.MS.ID.555763.php>
- [13] « Novel textile structures for enhanced bending performance in durable composite materials | Request PDF », *ResearchGate*, déc. 2025, doi: 10.1680/jemmr.25.00031.
- [14] V. Zogbochi, P. K. Chetangny, M. Medewou, S. Houndedako, G. Barbier, et D. Chamagne, « Optimization of Stirling generator for the production of electric energy using non-aggregate methods », *Sci. Afr.*, vol. 27, p. e02540, mars 2025, doi: 10.1016/j.sciaf.2025.e02540.
- [15] A.-S. Schuller *et al.*, « Optimization of the Electrospinning Process to Create an Active Bilayer Nanostructured Wound Dressing Based of PLA and Ibuprofen », *J. Appl. Polym. Sci.*, vol. 142, n° 45, p. e57726, 2025, doi: 10.1002/app.57726.
- [16] J. Hu, X. Legrand, et P. Wang, « Optimizing continuous fiber-reinforced textile preforms forming: Minimizing wrinkling through precision slitting », *Thin-Walled Struct.*, vol. 210, p. 113052, mai 2025, doi: 10.1016/j.tws.2025.113052.

- [17] « (PDF) 3D Weaving Process for Composite Reinforcements: Critical Yarn Crossings », *ResearchGate*, sept. 2025, doi: 10.1007/s10443-025-10321-9.
- [18] « (PDF) Analysis and optimization of the deformability of flax fiber nonwoven tapes during the tape-laying process », *ResearchGate*, sept. 2025, doi: 10.1007/s00170-025-15351-y.
- [19] « (PDF) Mechanical Performance of Thoracic Aortic Stent-Grafts: An In Vitro and In Silico Study », *ResearchGate*, déc. 2025, doi: 10.1007/s10439-025-03949-y.
- [20] W. Mahjoub et O. Harzallah, « Physical and Mechanical Characterization of Flax Fibers: From Elementary Fiber to Yarn », *Fibers*, vol. 13, n° 7, p. 87, juill. 2025, doi: 10.3390/fib13070087.
- [21] A. R. Asaad, F. Heim, C. Pidancier, et C. Jung, « Stent segments to improve the compliance of textile vascular grafts: preliminary assessment », *Emerg. Mater. Res.*, p. 1-12, déc. 2025, doi: 10.1680/jemmr.25.00076.
- [22] S. M. Anafack *et al.*, « Study of the Physical and Chemical Properties of Banana Peduncle Fibers of the Cultivar “William Cavendish”: Influence of Extraction Techniques », *Fibers*, vol. 13, n° 11, p. 153, nov. 2025, doi: 10.3390/fib13110153.